

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date 30th October 2019
Revision date 10TH January 2020 Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture Preparat usuwający etykiety (Label Killer)
mixture
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use Removing old labels.
Mixture uses advised against The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
- Manufacturer**
- | | |
|-----------------------------|--|
| Name or trade name | Platinet S.A |
| Address | ul. Tadeusza Śliwiaka 48, Kraków, 30-798
Poland |
| Identification number (CRN) | 120039390 |
| VAT Reg No | 679 28 44 218 |
| Phone | 12 65 10 505 |
| E-mail | handlowy@platinet.pl |
| Web address | www.platinet.pl |
- Competent person responsible for the safety data sheet**
- | | |
|--------|----------------------|
| Name | Platinet S.A |
| E-mail | handlowy@platinet.pl |
- 1.4. Emergency telephone number**
112 National Health Service (NHS) 111
National poisoning information centre Scotland, NHS 24: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Asp. Tox. 1, H304
Skin Irrit. 2, H315
Skin Sens. 1, H317
Eye Irrit. 2, H319
STOT SE 3, H336
Repr. 2, H361d
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Causes serious eye irritation. May cause drowsiness or dizziness. May cause an allergic skin reaction. Suspected of damaging the unborn child. May be fatal if swallowed and enters airways. Causes skin irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram



Signal word

Danger

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date 30th October 2019
Revision date 10th of January 2020 Version 1.0

Hazardous substances

isopropanol
3-Carene (cf. terpenes)
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
toluene
turpentine, oil
n-hexane
cyclohexane

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container to according to applicable regulations.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	38,5-44	Flam. Gas 1, H220 Press. Gas, H280	
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25-XXXX	isopropanol	20-30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	1
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	Propane	11-16,5	Flam. Gas 1, H220 Press. Gas, H280	

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date	30th October 2019			
Revision date	10 th of January 2020	Version	1.0	
Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
CAS: 13466-78-9 EC: 236-719-3	3-Carene (cf. terpenes)	5-10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Skin Sens. 1, H317	
EC: 920-107-4	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	5-10	Asp. Tox. 1, H304 EUH 066	
Index: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 Registration number: 01-2119471310-51-XXXX	toluene	3-5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2, H361d STOT RE 2, H373	1, 2
Index: 650-002-00-6 CAS: 8006-64-2 EC: 232-350-7	turpentine, oil	1-5	Flam. Liq. 3, H226 Acute Tox. 4, H302, H312, H332 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411	1
Index: 601-037-00-0 CAS: 110-54-3 EC: 203-777-6 Registration number: 01-2119474209-33-XXXX	n-hexane	0,9-4,5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411 Specific concentration limit: STOT RE 2, H373: C ≥ 5 %	1
Index: 601-017-00-1 CAS: 110-82-7 EC: 203-806-2	cyclohexane	<0,225	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	1, 2

Notes

- 1 Substance for which exposure limits of Community for working environment exist.
- 2 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date	30th October 2019	Version	1.0
Revision date	10 th of January 2020		

If swallowed

DO NOT INDUCE VOMITING! If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause drowsiness or dizziness.

If on skin

May cause an allergic skin reaction.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale gases and vapours. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Ventilate the room. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date 30th October 2019
Revision date 10th of January 2020 Version 1.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale gases and vapours. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Obtain special instructions before use. Wash hands and exposed parts of the body thoroughly after handling. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Substance name (component)	Type	Time of exposure	Value	Note	Source
toluene (CAS: 108-88-3)	OEL	8 hours	192 mg/m ³	skin	EU limits
	OEL	8 hours	50 ppm	skin	
	OEL	Short-term	384 mg/m ³	skin	
	OEL	Short-term	100 ppm	skin	
n-hexane (CAS: 110-54-3)	OEL	8 hours	72 mg/m ³		EU limits
	OEL	8 hours	20 ppm		
cyclohexane (CAS: 110-82-7)	OEL	8 hours	700 mg/m ³		EU limits
	OEL	8 hours	200 ppm		

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
isopropanol (CAS: 67-63-0)	WEL	8 hours	999 mg/m ³		GBR
	WEL	1 hour	1250 mg/m ³		
	WEL	8 hours	400 ppm		
	WEL	1 hour	500 ppm		
toluene (CAS: 108-88-3)	WEL	8 hours	191 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	1 hour	384 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date	30th October 2019	Version	1.0
Revision date	10 th of January 2020		

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
toluene (CAS: 108-88-3)	WEL	8 hours	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	1 hour	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
turpentine, oil (CAS: 8006-64-2)	WEL	8 hours	566 mg/m ³		GBR
	WEL	1 hour	850 mg/m ³		
	WEL	8 hours	100 ppm		
	WEL	1 hour	150 ppm		
n-hexane (CAS: 110-54-3)	WEL	8 hours	72 mg/m ³		GBR
	WEL	8 hours	20 ppm		
cyclohexane (CAS: 110-82-7)	WEL	8 hours	350 mg/m ³		GBR
	WEL	1 hour	1050 mg/m ³		
	WEL	8 hours	100 ppm		
	WEL	1 hour	300 ppm		

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date	30th October 2019	Version	1.0
Revision date	10 th of January 2020		

DNEL

isopropanol

Workers / consumers	Route of exposure	Value	Effect	Determining method
Workers	Inhalation	500 mg/m ³	Systemic chronic effects	
Workers	Dermal	888 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	89 mg/m ³	Systemic chronic effects	
Consumers	Dermal	319 mg/kg bw/day	Systemic chronic effects	
Consumers	Oral	26 mg/kg bw/day	Systemic chronic effects	

toluene

Workers / consumers	Route of exposure	Value	Effect	Determining method
Consumers	Oral	8.13 mg/m ³	Systemic chronic effects	
Consumers	Inhalation	226 mg/m ³	Systemic acute effects	
Workers	Inhalation	384 mg/m ³	Systemic acute effects	
Consumers	Inhalation	56.5 mg/m ³	Systemic chronic effects	
Workers	Inhalation	192 mg/m ³	Systemic chronic effects	
Consumers	Dermal	226 mg/kg/24hour	Systemic chronic effects	
Workers	Dermal	384 mg/kg/24hour	Systemic chronic effects	

PNEC

isopropanol

Route of exposure	Value	Determining method
Drinking water	140.9 mg/l	
Seawater	140.9 mg/l	
Freshwater sediment	552 mg/kg of dry substance	
Freshwater environment	552 mg/kg of dry substance	
Soil (agricultural)	28 mg/kg of dry substance	

toluene

Route of exposure	Value	Determining method
Drinking water	680 mg/l	
Seawater	680 mg/l	
Sea sediments	16.39 mg/kg	
Freshwater sediment	16.39 mg/kg	
Soil (agricultural)	2.89 mg/kg	
Microorganisms in wastewater treatment plants	13.61 mg/l	

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date 30th October 2019
Revision date 10th of January 2020 Version 1.0

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Respirator.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	spray
Physical state	gas at 20°C
color	data not available
Odour	data not available
Odour threshold	data not available
pH	data not available
Melting point/freezing point	data not available
Initial boiling point and boiling range	data not available
Flash point	data not available
Evaporation rate	non-applicable
Flammability (solid, gas)	Extremely flammable aerosol.
Upper/lower flammability or explosive limits	
flammability limits	data not available
explosive limits	data not available
Vapour pressure	data not available
Vapour density	data not available
Relative density	data not available
Solubility(ies)	
solubility in water	not available
solubility in fats	not available
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Explosive properties	data not available
Oxidising properties	data not available

9.2. Other information

Density	data not available
ignition temperature	data not available

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date 30th October 2019
Revision date 10th of January 2020 Version 1.0

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

cyclohexane

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	12000 mg/kg		Rat (Rattus norvegicus)	
Dermal	LD ₅₀	>18000 mg/kg		Rabbit	

isopropanol

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Inhalation	LC ₅₀	>5 mg/l	4 hour	Rat	
Oral	LD ₅₀	>2000 mg/kg		Rat	
Skin	LD ₅₀	>2000 mg/kg		Rabbit	

n-hexane

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	28700 mg/kg		Rat (Rattus norvegicus)	
Dermal	LD ₅₀	3295 mg/kg		Rabbit	

toluene

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	5580 mg/kg		Rat	
Dermal	LD ₅₀	>5580 mg/kg		Rabbit	
Inhalation	LC ₅₀	>20000 mg/m ³	4 hour	Rat	

Skin corrosion/irritation

Causes skin irritation.

toluene

Route of exposure	Result	Time of exposure	Species
	Irritating		

turpentine, oil

Route of exposure	Result	Time of exposure	Species
	Irritating		

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date 30th October 2019
Revision date 10th of January 2020 Version 1.0

Serious eye damage/irritation

Causes serious eye irritation.

Sensitization

turpentine, oil

Route of exposure	Result	Time of exposure	Species	Sex
	Sensitizing			

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways. Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time.

toluene

Route of exposure	Result	Time of exposure	Species	Sex
	Negative			

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

isopropanol

Parameter	Value	Time of exposure	Species	Environment
LC ₅₀	>100 mg/l	48 hour	Fishes (Leuciscus idus)	
EC ₅₀	>100 mg/l	48 hour	Daphnia (Daphnia magna)	
EC ₅₀	>100 mg/l	72 hour	Algae (Scenedesmus subspicatus)	

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date	30th October 2019	Version	1.0
Revision date	10 th of January 2020		

n-hexane

Parameter	Value	Time of exposure	Species	Environment
LC ₅₀	3900 mg/ml	48 hour	Invertebrates (Daphnia magna)	
NOEL	30000 mg/ml	72 hour	Algae and other aquatic plants (Pseudokirchneriella subcapitata)	
LC ₅₀	>1000 µg/l	48 hour	Fishes	

toluene

Parameter	Value	Time of exposure	Species	Environment
LC ₅₀	13 mg/l	96 hour	Fishes (Carassius auratus)	
LC ₅₀	59.3 mg/l	96 hour	Fishes (Poecilia reticulata)	
LC ₅₀	6.3 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	
EC ₅₀	10 mg/l	48 hour	Invertebrates (Daphnia magna)	
EC ₅₀	32 mg/l	72 hour	Algae (Selenastrum capricornutum)	

Chronic toxicity

toluene

Parameter	Value	Time of exposure	Species	Environment
LOEC	1.6 mg/l	32 day	Fishes (Pimephales promelas)	Freshwater
LOEC	3.5 mg/l	32 day	Fishes (Oncorhynchus mykiss)	Freshwater
LOEC	5.3 mg/l	28 day	Fishes	Salt water
NOAEC	3.1 mg/l	28 day	Fishes	Salt water
EC ₅₀	391 mg/l	24 hour	Aquatic mikroorganisms (Tetrahymena pyriformis)	
IC ₅₀	520 mg/l	15 hour		Activated sludge

12.2. Persistence and degradability

Biodegradability

toluene

Parameter	Value	Time of exposure	Environment	Result
		2,59 day		Easily biodegradable

Not available.

12.3. Bioaccumulative potential

toluene

Parameter	Value	Time of exposure	Species	Environment	Surrounding temperature [°C]
Log Pow	2.73				

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date	30th October 2019	Version	1.0
Revision date	10 th of January 2020		

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

16 05 04 gases in pressure containers (including halons) containing hazardous substances *

Packaging waste type code

15 01 11 metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not available

14.5. Environmental hazards

not available

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not available

Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1



SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date 30th October 2019
Revision date 10th of January 2020 Version 1.0

Air transport - ICAO/IATA

Packaging instructions passenger 203
Cargo packaging instructions 203

Marine transport - IMDG

EmS (emergency plan) F-D, S-U
MFAG 620

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

cyclohexane

Restriction	Conditions of restriction
57	<p>1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of neoprene-based contact adhesives in concentrations equal to or greater than 0,1 % by weight in package sizes greater than 350 g.</p> <p>2. Neoprene-based contact adhesives containing cyclohexane and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.</p> <p>3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that neoprene-based contact adhesives containing cyclohexane in concentrations equal to or greater than 0,1 % by weight that are placed on the market for supply to the general public after 27 December 2010 are visibly, legibly and indelibly marked as follows:</p> <p>"— This product is not to be used under conditions of poor ventilation. — This product is not to be used for carpet laying."</p>

toluene

Restriction	Conditions of restriction
48	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date	30th October 2019	Version	1.0
Revision date	10 th of January 2020		

H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to according to applicable regulations.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

A list of additional standard phrases used in the safety data sheet

EUH 066	Repeated exposure may cause skin dryness or cracking.
---------	---

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

PLATINET LABEL REMOVER SPRAY 400ML

Creation date	30th October 2019	Version	1.0
Revision date	10 th of January 2020		

NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative

Acute Tox.	Acute toxicity
Aerosol	Aerosol
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.